GUARDIAN Blackout



All colors available in same color on both sides. MOQ may apply.

friedland shades

Custom colors available. Minimum production runs will apply.

FABRIC TECHNICAL **SPECIFICATIONS**

FABRIC COMPOSITION: 3 Ply (62.1% Vinyl, 31.6% Fiberglass, 6.2% Proprietary Coating)

THICKNESS: 13.1 mil.

FABRIC THREAD COUNT: 59 threads per sq/in. (23 per sq/cm)

FLAME RESISTANCE: NFPA No. 701-2019 Test Method 1

FABRIC WEIGHT: 12.8 oz/sq-yd (436.7 g/sq met)

BREAKING STRENGTH: 299 Warp Direction 299 Fill Direction

UV OPACITY: 100% Blackout

USAGE: Roller Shade Fabrics

CERTIFICATIONS:

- ASTM D3335-85a—Lead Testing
 ASTM Method G-21-15—Resistance to Fungi

WASHABILITY: Dust with a damp cloth. Scrub with warm water, mild detergent, and gentle rubbing.

FABRIC WARRANTY: Guardian blackout fabric is guaranteed to be free of any manufacturing defects for period of 5 years.









PRODUCT FEATURES

Decorative woven look and feel.

Incredibly durable and stable.

Ability to withstand high heat and direct light. Will not crack, yellow, or develop pin-holes.

Great for commercial, institutional, hospitality, and residential applications.

Fabric Made in U.S.A

Custom colors available for contract orders. Minimum production runs will apply

friedland shades

17 Industrial Drive, Cliffwood Beach, NJ 07735 P (732) 290-9800 • sales@rfbcorp.com www.friedlandshades.com @friedlandshades

